

Gitlab - A git server

Docker compose

```
services:
  gitlab:
    image: 'gitlab/gitlab-ce:latest'
    restart: always
    hostname: 'gitlab'
    labels:
      - "traefik.enable=true"
      - "traefik.docker.network=webv2"
      - "traefik.http.routers.gitlab.rule=Host(`gitlab.domain.com`)"
      - "traefik.http.routers.gitlab.entrypoints=web-insecure"
      - "traefik.http.routers.gitlab.middlewares=redirect@file"
      - "traefik.http.routers.gitlab-secured.rule=Host(`gitlab.domain.com`)"
      - "traefik.http.routers.gitlab-secured.tls=true"
      - "traefik.http.routers.gitlab-secured.tls.certResolver=main"
      - "traefik.http.routers.gitlab-secured.entrypoints=web-secure"
      - "traefik.http.services.gitlab.loadBalancer.server.port=80"
      - "traefik.http.routers.gitlab.service=gitlab"
      - "traefik.http.routers.gitlab-secured.service=gitlab"
      - "traefik.http.routers.gitprom.rule=Host(`gitprom.domain.com`)"
      - "traefik.http.routers.gitprom.entrypoints=web-insecure"
      - "traefik.http.routers.gitprom.middlewares=redirect@file"
      - "traefik.http.routers.gitprom-secured.rule=Host(`gitprom.domain.com`)"
      - "traefik.http.routers.gitprom-secured.tls=true"
      - "traefik.http.routers.gitprom-secured.tls.certResolver=main"
      - "traefik.http.routers.gitprom-secured.entrypoints=web-secure"
      - "traefik.http.services.gitprom.loadBalancer.server.port=9090"
      - "traefik.http.routers.gitprom.service=gitprom"
      - "traefik.http.routers.gitprom-secured.service=gitprom"
    environment:
      GITLAB_OMNIBUS_CONFIG: |
        external_url 'https://gitlab.domain.com'
        nginx['listen_https'] = false
        nginx['listen_port'] = 80
        prometheus['listen_address'] = 'localhost:9090'
```

volumes:

- /path/to/config:/etc/gitlab
- /path/to/logs:/var/log/gitlab
- /path/to/data:/var/opt/gitlab

networks:

- webv2

version: "2"

Revision #2

Created 11 January 2024 13:30:19 by Andreas Greiner

Updated 11 January 2024 13:31:08 by Andreas Greiner